Flexy Vision 10 X86

Panel PC with 10.1” LCD display based on the Intel® Atom® X Series and Intel® Celeron J / N Series (formerly Apollo Lake) Processors

Flexibility Meets Style For Endless Visual Display Applications

AI-ENABLED WITH CLEA

HIGHLIGHTS

CPU
Intel® Celeron® / Atom™ (Dual / Quad Core processors)

CONNECTIVITY
2x GbE; 2x RS-232 or RS-485 on DB-9 connector; 2x USB 3.0 + 2x USB 2.0 ports

GRAPHICS
50K Hours 1280x800 LVDS display with projected capacitive touchscreen integrated

MEMORY
Soldered-down LPDDR4 memory, up to 8GB total

Windows 10 Enterprise · Windows 10 IoT Core · Linux

MAIN FIELDS OF APPLICATION

Digital Signage - Infotainment · Industrial Automation · Vending

FEATURES

Processor	Intel® Atom® **x5-E3930** Dual Core @1.3 GHz (Burst 1.8GHz), 2MB L2 Cache, 6.5W TDP Intel® Atom® **x5-E3940** Quad Core @1.6 GHz (Burst 1.8GHz), 2MB L2 Cache, 9.5W TDP Intel® Atom® **x7-E3950** Quad Core @1.6 GHz (Burst 2.0GHz), 2MB L2 Cache, 12W TDP Intel® Pentium® **N4200** Quad Core @1.1GHz (Burst 2.5GHz), 2MB L2 Cache, 6W TDP Intel® Celeron® **N3350** Dual Core @1.1GHz (Burst 2.4GHz), 2MB L2 Cache, 6W TDP Intel® Celeron® **J3455** Quad Core @1.5GHz (Burst 2.3GHz), 2MB L2Cache, 10W TDP Intel® Celeron® **J3355** Dual Core @2.0GHz (Burst 2.5GHz), 2MB L2Cache, 10W TD
Memory	Soldered-down LPDDR4 memory Dual/Quad Channel, up to 8GB total, 32-bit interface
Embedded Graphics	Integrated Intel® HD Graphics 500 series controller with up to 18 Execution Units Three Independent displays supported HW decoding of HEVC(H.265), H.264, MVC, VP8, VP9, MPEG2, VC-1, WMV9, JPEG/MJPEG formats HW encoding of HEVC(H.265), H.264, MVC, VP8, VP9 and JPEG/MJPEG formats
Video Section	10.1” LVDS display, resolution 1280x800, LED lifetime 50K hours life min, 340cd/m2 min. brightness P-Cap (Projected Capacitive touch screen), with 3.0mm glass cover Glass Hardness IK07, Surface Hardness 7H

Video Interfaces	HDMI Connector DP++ Connector
Mass Storage	eMMC 5.0 drive soldered on-board, up to 64GB M.2 Key B slot for optional SSD drive, up to 512GB
Networking	2x Gigabit Ethernet port M.2 WWAN Connectivity Slot for accessory 4G modules (excludes SSD Drive) M.2 WLAN Connectivity Slot for accessory WiFi/BT module
USB	2x USB 3.0 Host ports on Type-A sockets 2 x USB 2.0 Host ports on Dual Type-A socket
Serial Ports	2x multistandard RS-232 /RS-422/RS-485 ports on DB-9 connectors
Other Interfaces	Power ON Button with integrated LED Optional TPM 2.0 onboard
Power Supply	Main Power: $12V_{DC}$ Power In connectors: DC Power Jack
Operating System	Windows 10 IOT Linux
Operating Temperature*	0°C ÷ 50°C
Dimensions	269,5 x 188,1 x 58mm

*Measured at any point of the heatspreader/heatsink during any and all times (including start-up). Actual temperature will widely depend on application, enclosure and/or environment. Upon customer to consider specific cooling solutions for the final system to keep the heatspreader temperature in the range indicated.

Information subject to change. Please visit www.edge.seco.com to find the latest version of this datasheet

Flexy Vision 10 X86

Panel PC with 10.1” LCD display based on the Intel® Atom® X Series and Intel® Celeron J / N Series (formerly Apollo Lake) Processors

Display touch kit specifications

- P-Cap (Projected-Capacitive touch technology) - Glass cover
- Glass Hardness: IK07
- Surface Hardness: 7H
- Thickness: 3.0mm
- Air bonding

LCD General specifications

Item	Specification
LCD Size	10.1”
Resolution	1280x800
Display Mode	Advanced Hyper-Viewing Angle (AHVA), Normally Black
Display colours	16.7M colours
Pixel pitch	0.1695 (H) x 0.1695 (V) mm
Active Area	216.96 (H) x 135.6 (V) mm
Module Size	227.91 (H) x 148 (V) x 7.75 (T) mm, max
Pixel Arrangement	RGB Vertical Stripe
Surface Treatment	Anti-Glare, Anti Fingerprint
Interface	LVDS
Luminance	340cd/m2 (min.), 420cd/m2 (Typ.)
Backlight Power Consumption	3.024W (Max)
Panel Power Consumption	1W (Max)

Optical specifications

Item	Symbol	Condition	Values (degree)		
			Min.	Typ.	Max.
Viewing angle (CR≥ 10)	θ_L	Φ=180° (9 o’clock)	80	89	-
	θ_R	Φ=0° (3 o’clock)	80	89	-
	θ_T	Φ=90° (12 o’clock)	80	89	-
	θ_B	Φ=270° (6 o’clock)	80	89	-

Panel mount/VESA mount*









* all dimension are in mm

Information subject to change. Please visit www.edge.seco.com to find the latest version of this datasheet