



SBC-pITX-TWL

Pico-ITX SBC with the Intel® AtomTMProcessor "Twin Lake" Embedded PC Client N Series for the Edge

Low-power, compact, and versatile - perfect for industrial automation and IoT edge solutions.



HIGHLIGHTS

CPU Intel® AtomTMProcessor "Twin Lake" Embedded PC Client N Serie	CONNECTIVITY Up to 2x 2.5GbE, M.2 E-Key (WiFi+BT), M.2 B-Key (WWAN)
GRAPHICS Up to 2 independent displays (LVDS/eDP + HDMI) Integrated Intel® Graphics controller with up to 32 EU 4K60 HW decoding and encoding of HEVC (H.265), AVC (H.264), VP9, SCC, AVI (decoding only)	MEMORY LPDDR5-5200 Soldered Down Memory, Up to 16 GB, with iBECC support

Windows 11
IoT EnterpriseEDGEHOG
ALL-IN-ONE IoT PLATFORMHDMI®
HIGH-DEFINITION MULTIMEDIA INTERFACE

MAIN FIELDS OF APPLICATION



Medical



Industrial Automation



Smart Devices Smart Buildings & Smart Cities



FEATURES


Processor Intel Processor N150 Quad Core @0.8GHz (3.6GHz Turbo 6W TDP) Intel Processor N250 Quad Core @1.3GHz (3.8GHz Turbo 6W TDP) Intel Processor N355 Quad Core @1.0/1.9GHz (3.9GHz Turbo) 9/15W TDP	Networking Up to 2x 2.5GbE Ethernet LAN ports available on 2x single RJ45 connectors M.2 WiFi+BT Connectivity Slot (Socket 1 Key E type 2230) M.2 WWAN Connectivity Slot (Socket 2 Key B size 2242/3042/3052/2260) coupled to on-board Nano-SIM slot**
Memory LPDDR5-5200 Soldered Down Memory, Up to 16 GB, with iBECC support	USB 2x SuperSpeed USB 10Gbps ports on Dual type-A socket 3x USB 2.0 ports on internal pin headers
Graphics Integrated Intel® Graphics driven by Intel® Xe architecture: Intel® Processor N355 with 32 Execution Units Intel® Processor N250 with 32 Execution Units Intel® Processor N150 with 24 Execution Units AVX256 & VNNI support for faster AI inference and media transcoding 3D API DirectX 12.1, OpenGL 4.6, Mesa 3D, Vulkan 1.2 4K60 HW decoding and encoding of HEVC (H.265), AVC (H.264), VP9, SCC, AVI (decoding only)	Audio HD Audio Codec, Tempo Semicon 92HD68D3 S/PDIF Out and Mic In on internal pin header
Video Interfaces eDP 1.4b or Single/Dual Channel 18/24bit LVDS interface HDMI 1.4b interface	Serial Ports 2x Serial Ports (RS-232/RS-422/RS-485) on internal pin header
Video Resolution 1x LVDS, Dual Channel 18/24-bit, up to 1920 x 1080 1x HDMI 1.4b, up to 3840 x 2160 x 24bpp@20-30Hz eDP, Up to 4096 x 2304	I2C 2x I2C interfaces available on expansion internal header 8x GP I/Os interfaces available on expansion internal header Other Interfaces 1x SPI interface available on expansion internal header Optional TPM 1.2/2.0 Module on-board FAN connector RST_BTN#, PWR_BTN# and activity LED signals on front panel pin header
Mass Storage Optional eMMC 5.1 drive soldered on-board, up to 128GB 1x SATA Gen3 7p M connector with + 4p M power connector 1x M.2 SATA SSD Slot (Socket 2 Key B size 2242/3042/3052/2260)**	Power Supply 12V _{DC} Cabled coin cell battery for RTC Operating System Microsoft® Windows 11 IoT Enterprise LTSC Edgehog OS Operating Temperature* 0°C - +60°C (Commercial version)
	Dimensions 100x72mm (3.93" x 2.83")

**SATA SSD and WWAN functionalities share the same slot and are therefore mutually exclusive.

SBC-pITX-TWL

Pico-ITX SBC with the Intel® Atom™ Processor "Twin Lake" Embedded PC Client N Series for the Edge

BLOCK DIAGRAM




Streamline and expedite your edge computing implementations

Clea OS

A flexible operating system that adapts to your needs, thanks to the customization tool and Docker support. Reliability and security are built-in through a dual-partition system and native integration with Exein's robust AI-based protection.

Clea Astarte

Integrate third-party services, simplify data flows and analysis, and enhance business efficiency by enabling easy and fast utilization of AI.





Clea Edgehog

Update, configure, and manage remote devices. Optimize time and costs to maximize operational efficiency and security without the need for costly field interventions.

Clea Portal

Analyze data from remote devices, customize the user experience with applications tailored to user needs, and manage user rights, company access, and tenant privileges.



Scan to know more about our solution

Clea OS



Clea DOCS

